



Model	6212M/C3VL0241	Reference speed	13000 r/min
Manufacturers	TFL	Coating	Insulation coating on outer ring
Bore diameter (d)	60.0 mm	Product Category	Single Row Deep Groove Ball Bearing
Outside diameter (D)	110.0 mm	Breakdown Voltage (DC)	1000 ~3000 V
Width (B)	22.0 mm	Layer thickness	100~500 μm
Net Weight	0.954 kg	Electrical Resistance	50~200 MΩ
Basic dynamic load rating	57.0 kN	Cage material	Brass cage
Basic static load rating	36.5 kN	Radial internal clearance	C3



TFL Bearings Manufacturing Co., Ltd.

Building 2, Lushang Phoenix Plaza, 521 Jingde Road, Licheng District, Jinan City, Shandong Province, China
<https://insulated-bearings.com>
info@insulated-bearings.com
 0086 15806631151

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. TFL makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MODEL	6212M/C3VL0241
SIZE	Deep Groove Ball Bearings Single Row, 60.0 mm X 110.0 mm X 22.0 mm
BRAND	TFL